662AQ Time Zone Clock

www.brgprecsion.com

## User Changeable Multi-Color LED Colors

| 07:18     | 1 1:15      | 17:16              | 20:15        | <b>0 2: 16</b> |
|-----------|-------------|--------------------|--------------|----------------|
| Hawaii    | Central     | London             | baghdad      | n. korea       |
| 08:15     | 12:15       | 17:16              | 20:18        | <u>02:18</u>   |
| Fairbanks | EASTERN     | zulu               | qatar        | токуо          |
| 09:18     | 15:16       | 18:15              | 2048         | 04:15          |
| pacific   | sao paulo   | Berlin             | iran         | Sydney         |
| 18:18     | 15:15       | <mark>20:18</mark> | <b>2 145</b> | 05:18          |
| mountain  | E.GREENLAND | моscow             | afghanistan  | NEW ZEALAND    |

Model 662AQ - 1.8" time, 0.75" zone labels, 20 Zone - 4 x 5 layout

## **Specifications**

| Display:               | Twenty zone - $4 \times 5$ layout, 4 digit user changeable multi-color bar segment LED time display with 0.75" white vinyl zone labels.                                     |  |  |  |
|------------------------|---|--|--|--|
| Display Format:        | 12 or 24 hour format, Numeric Date, (American or European), Numeric Year, and Julian Date   |  |  |  |
| Clock Accuracy:        | BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required. |  |  |  |
| Manual Controls:       | Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.   |  |  |  |
| Operating Mode:        | Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.   |  |  |  |
| Digit Height:          | 1.8" bar segment LEDs for time  |  |  |  |
| Visibility:            | Up to 40 feet   |  |  |  |
| Power Requirement:     | 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.   |  |  |  |
| Dimensions:            | 24.25" Tall x 50.25" Wide x 3.25" Deep  |  |  |  |
| Operating Temperature: | -32° F to 120°F   |  |  |  |
| Humidity:              | 0% to 95% Non-condensing  |  |  |  |
| Construction:          | Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.   |  |  |  |

## User Changeable Multi-Color LED Colors

| 12:25<br>mountain | 13:25<br>central | IH:25<br>EASTERN | 88:25<br>HAWAII |         | CC:25<br>GERMANY | 2 1:25<br>IRAQ |
|-------------------|------------------|------------------|-----------------|---------|------------------|----------------|
| <br>Red           | Green            | Blue             | Yellow          | Magenta | Cyan             | White          |



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 662AQ Spec Sheet Rev 1.0 10.31.2022



600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080