663V Time Zone Clock

www.brgprecsion.com

User Changeable Multi-Color LED Colors

| PACIFIC | / ¦:35 eastern | 1 <i>6:35</i> zulu | 18:35 kuwait | 18:35 djibouti | 19:35 iraq | | |
|---|--|---|-----------------|-------------------|---------------|-------|--|
| 08 15 i | 08 15 | 08/15 | 08 15 | 08/15 | 08/15 | 08 15 | |
| Model 663V- 4.0" time, 1.5" vinyl zone labels, 7 zones Specifications | | | | | | | |
| Display: | Seven zone, four digit user changeable multi-color bar segment LED time and date displays with 1.5" white vinyl zone labels. | | | | | | |
| Display Format: | : 12 or 24 ho | 12 or 24 hour format, Numeric Date, (American or European), Numeric Year, and Julian Date | | | | | |
| Clock Accuracy: | | BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required. | | | | | |
| Manual Controls: | | Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options. | | | | | |
| Operating Mode: | : Time zone | Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets. | | | | | |
| Digit Height: | 4.0" bar segment LEDs for time | | | | | | |
| Visibility: | Up to 100 feet | | | | | | |
| Power Requirement: | 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard. | | | | | | |
| Dimensions: | 18.25" Tall x 96.25" Wide x 3.25" Deep | | | | | | |
| Operating Temperature: | -32° F to 120°F | | | | | | |
| Humidity: | : 0% to 95% | 0% to 95% Non-condensing | | | | | |
| Construction: | : Black anoc | Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included. | | | | | |

User Changeable Multi-Color LED Colors





Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2023, BRG Precision Products, All rights reserved, 663V Spec Sheet Rev 1.0 06.22.2023



600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080