

www.brgprecsion.com

With Scrolling Message Display

User Changeable Multi-Color LED Colors



Model 669E - 2.5" time, 1.0" white vinyl zone labels, 2.0" dot matrix message display 24" wide, 2 zones

Specifications

Display:	Two zone, 4 digit user changeable multi-color bar segment LED time displays with white vinyl zone labels and 2" x 24" scrolling message display.
Display Format:	12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date
Clock Accuracy:	BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.
Computer Interface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.
Digit Height:	2.5" bar segment LEDs for time and 2.0" LEDs for message display.
Visibility:	Up to 75 feet
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.
Dimensions:	14.25" Tall x 30.25" Wide x 3.25" Deep
Operating Temperature:	-32° F to 120°F
Humidity:	0% to 95% Non-condensing
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.

User Changeable Multi-Color LED Colors

13:25

EASTERN

Blue

CENTRAL

Green

NTAIN

Red

88:25

HAWAI

Yellow



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2023, BRG Precision Products, All rights reserved, 669E Spec Sheet Rev 1.0 06.27.2023



22:55

AFGHANISTAN

Magenta

20:25

GERMAN

Cyan

2 1:2

IRAC

White

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080