



# 3618E Time Zone Clock

with Date

www.brgprecision.com

## Specifications

## User Changeable Multi-Color LED Colors

**Display:** Six zone, 4 digit, 7 segment user changeable multi-color bar segment LED time displays with 15 character dot matrix LED zone labels and date.

**Zone Capacity:** Up to 18 time zones can be displayed by page flipping zones 3 times.

**Display Format:** 12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German and Spanish). Alpha dates and year formats can be laid out in any order.

**Clock Accuracy:** BRG Time Zone Clocks will display the correct time for the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.

**Computer Interface:** USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.

**Manual Controls:** Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.

**Operating Mode:** Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.

**Digit Height:** 1.8" bar segment LEDs for time, 2.0" dot matrix LEDs for date and 1.2" dot matrix LEDs for zone labels.

**Visibility:** Up to 40 feet

**Power Requirement:** 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.

**Dimensions:** 54.25" Tall x 15.25" Wide x 3.25" Deep

**Operating Temperature:** -32° F to 120° F


**Humidity:** 0% to 95% Non-condensing

**Construction:** Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.



Model 3618E- 1.8" time, 1.2" zone labels, 2.0" date, 6 zones

## User Changeable Multi-Color LED Colors



Email: [sales@brgproducts.com](mailto:sales@brgproducts.com)  
Web Site: <https://www.brgprecision.com>

Copyright 2022, BRG Precision Products, All rights reserved,  
3618E Spec Sheet Rev 1.0 10.27.2022



600 N River Street • Derby, Kansas 67037  
800-295-0220 • 316-788-2000  
Fax: 316-788-7080