



6618Q Time Zone Clock

With Alpha-Numeric Calendar Display

www.brgprecision.com

User Changeable Multi-Color LED Colors



Model 6618Q - 1.8" time, 1.2" zone labels, 1.2" 20 Character Date, 6 zones

Specifications

- Display:** Six zone, 5 digit user changeable multi-color bar segment LED time displays with 10 character dot matrix LED zone labels and 20 character date.
- Zone Capacity:** Up to 18 time zones can be displayed by page flipping zones 3 times
- Display Format:** 12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date
- Clock Accuracy:** BRG Time Zone Clocks will display the correct time for the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.
- Computer Interface:** USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.
- Manual Controls:** Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.
- Operating Mode:** Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.
- Digit Height:** 1.8" bar segment LEDs for time, 1.2" dot matrix LEDs for zone labels and 1.2" dot matrix date.
- Visibility:** Up to 40 feet
- Power Requirement:** 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.
- Dimensions:** 10.25" Tall x 78.25" Wide x 3.25" Deep
- Operating Temperature:** -32° F to 120°F
- Humidity:** 0% to 95% Non-condensing
- Construction:** Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.

User Changeable Multi-Color LED Colors



Email: sales@brgproducts.com
Web Site: <https://www.brgprecision.com>

Copyright 2022, BRG Precision Products, All rights reserved,
6618Q Spec Sheet Rev 1.0 07.26.2022



600 N River Street • Derby, Kansas 67037
800-295-0220 • 316-788-2000
Fax: 316-788-7080