



## 662 Style Time Zone Clock



Model 662BH - 2.5" time,  
1.0" zone labels, 16 zones



Model 662A - 1.8" time, 0.75" zone labels, 6 zones



Model 662B - 1.8" time, 0.75" zone labels, 8 zones

The 662 series time zone clocks have user changeable multi-color bar-segment LED time with white vinyl zone labels below the time of each zone. 662 models can display between 4-24 time zones.

Each 662 clock comes standard with an OCXO oscillator, which is accurate to .06 seconds per year.

For easy clock management, an infrared (IR) remote control is included with every 662 model. An optional BRG Time Commander IR Touch Pad Remote control to use with all of your time zone clocks.

### Features:

- OCXO oscillator accurate to .06 seconds per year
- 1.8", 2.5" or 4.0" user changeable multi-color bar segment LEDs for displaying time\* (red, blue, green, yellow, magenta, cyan & white LED colors)
- 0.75", 1.0" or 1.5" white vinyl lettering for displaying zone names\*
- Models that display from 4 to 24 separate time zones\*
- 12 or 24 hour format
- DST and time zone offsets supported
- IR remote control included
- Black brushed Aluminum frame
- Multiple cord lengths available
- US, British, Australian or European plugs
- 100-240 VAC. 50-60 cycle power
- Available on GSA, contract GS-02F-0030U



### Oven Controlled Crystal Oscillator (OCXO)

- Accurate to 2 PPB (parts per Billion) or .06 seconds per year or about 1 second in 20 years.
- 1 thousand times more accurate than most competing clocks
- Eliminates the need for GPS or Network time synchronization for

# 662 Style Time Zone Clocks

Model	Zones	Time Display	Grid Layout		Viewing Distance	Dimensions		
			Rows	Columns		H	W	D
662S	4	1.8	2	2	40 ft.	12.25	20.25	3.25
662A	6	1.8	2	3	40 ft.	12.25	30.25	3.25
662B	8	1.8	2	4	40 ft.	12.25	40.25	3.25
662C	10	1.8	2	5	40 ft.	12.25	50.25	3.25
662AA	12	1.8	2	6	40 ft.	12.25	60.25	3.25
662AJ	14	1.8	2	7	40 ft.	12.25	70.25	3.25
662AK	16	1.8	2	8	40 ft.	12.25	80.25	3.25
662AL	18	1.8	2	9	40 ft.	12.25	90.25	3.25
662AD	6	1.8	3	2	40 ft.	18.25	20.25	3.25
662D	9	1.8	3	3	40 ft.	18.25	30.25	3.25
662E	12	1.8	3	4	40 ft.	18.25	40.25	3.25
662F	15	1.8	3	5	40 ft.	18.25	50.25	3.25
662AM	18	1.8	3	6	40 ft.	18.25	60.25	3.25
662AN	21	1.8	3	7	40 ft.	18.25	70.25	3.25
662AO	24	1.8	3	8	40 ft.	18.25	80.25	3.25
662V	8	1.8	4	2	40 ft.	24.25	20.25	3.25
662W	12	1.8	4	3	40 ft.	24.25	30.25	3.25
662AP	16	1.8	4	4	40 ft.	24.25	40.25	3.25
662AQ	20	1.8	4	5	40 ft.	24.25	50.25	3.25
662AR	24	1.8	4	6	40 ft.	24.25	60.25	3.25
662AG	10	1.8	5	2	40 ft.	30.25	20.25	3.25
662AS	15	1.8	5	3	40 ft.	30.25	30.25	3.25
662AT	20	1.8	5	4	40 ft.	30.25	40.25	3.25
662AU	12	1.8	6	2	40 ft.	36.25	20.25	3.25
662AV	18	1.8	6	3	40 ft.	36.25	30.25	3.25
662AW	24	1.8	6	4	40 ft.	36.25	40.25	3.25
662AX	14	1.8	7	2	40 ft.	42.25	20.25	3.25
662AY	21	1.8	7	3	40 ft.	42.25	30.25	3.25
662AZ	16	1.8	8	2	40 ft.	48.25	20.25	3.25
662BA	24	1.8	8	3	40 ft.	48.25	30.25	3.25
662BB	18	1.8	9	2	40 ft.	54.25	20.25	3.25

## Color Options



Red

Blue

Green

Yellow

Magenta

Cyan

White



Model	Zones	Time	Grid Layout		Viewing	Dimensions		
		Display	Rows	Columns	Distance	H	W	D
662T	4	2.5	2	2	75 ft.	16.25	24.25	3.25
662G	6	2.5	2	3	75 ft.	16.25	36.25	3.25
662H	8	2.5	2	4	75 ft.	16.25	48.25	3.25
662I	10	2.5	2	5	75 ft.	16.25	60.25	3.25
662AB	12	2.5	2	6	75 ft.	16.25	72.25	3.25
662BC	14	2.5	2	7	75 ft.	16.25	84.25	3.25
662BD	16	2.5	2	8	75 ft.	16.25	96.25	3.25
662AE	6	2.5	3	2	75 ft.	24.25	24.25	3.25
662J	9	2.5	3	3	75 ft.	24.25	36.25	3.25
662K	12	2.5	3	4	75 ft.	24.25	48.25	3.25
662L	15	2.5	3	5	75 ft.	24.25	60.25	3.25
662BE	18	2.5	3	6	75 ft.	24.25	72.25	3.25
662BF	21	2.5	3	7	75 ft.	24.25	84.25	3.25
662BG	24	2.5	3	8	75 ft.	24.25	96.25	3.25
662X	8	2.5	4	2	75 ft.	32.25	24.25	3.25
662Y	12	2.5	4	3	75 ft.	32.25	36.25	3.25
662BH	16	2.5	4	4	75 ft.	32.25	48.25	3.25
662BI	20	2.5	4	5	75 ft.	32.25	60.25	3.25
662BJ	24	2.5	4	6	75 ft.	32.25	72.25	3.25
662AH	10	2.5	5	2	75 ft.	40.25	24.25	3.25
662BK	15	2.5	5	3	75 ft.	40.25	36.25	3.25
662BL	20	2.5	5	4	75 ft.	40.25	48.25	3.25
662BM	12	2.5	6	2	75 ft.	48.25	24.25	3.25
662BN	18	2.5	6	3	75 ft.	48.25	36.25	3.25
662BO	24	2.5	6	4	75 ft.	48.25	48.25	3.25
662BP	14	2.5	7	2	75 ft.	56.25	24.25	3.25
662BQ	21	2.5	7	3	75 ft.	56.25	36.25	3.25
662BR	16	2.5	8	2	75 ft.	64.25	24.25	3.25
662BS	24	2.5	8	3	75 ft.	64.25	36.25	3.25
662U	4	4.0	2	2	100 ft.	20.25	30.25	3.25
662M	6	4.0	2	3	100 ft.	20.25	45.25	3.25
662N	8	4.0	2	4	100 ft.	20.25	60.25	3.25
662O	10	4.0	2	5	100 ft.	20.25	75.25	3.25
662AC	12	4.0	2	6	100 ft.	20.25	90.25	3.25
662AF	6	4.0	3	2	100 ft.	30.25	30.25	3.25
662P	9	4.0	3	3	100 ft.	30.25	45.25	3.25
662Q	12	4.0	3	4	100 ft.	30.25	60.25	3.25
662R	15	4.0	3	5	100 ft.	30.25	75.25	3.25
662BT	18	4.0	3	6	100 ft.	30.25	90.25	3.25
662Z	8	4.0	4	2	100 ft.	40.25	30.25	3.25
662BU	12	4.0	4	3	100 ft.	40.25	45.25	3.25
662BV	16	4.0	4	4	100 ft.	40.25	60.25	3.25
662BW	20	4.0	4	5	100 ft.	40.25	75.25	3.25
662BX	24	4.0	4	6	100 ft.	40.25	90.25	3.25
662AI	10	4.0	5	2	100 ft.	50.25	30.25	3.25
662BY	15	4.0	5	3	100 ft.	50.25	45.25	3.25
662BZ	12	4.0	6	2	100 ft.	60.25	30.25	3.25
662CA	18	4.0	6	3	100 ft.	60.25	45.25	3.25
662CB	14	4.0	7	2	100 ft.	70.25	30.25	3.25
662CC	21	4.0	7	3	100 ft.	70.25	45.25	3.25
662CD	16	4.0	8	2	100 ft.	80.25	30.25	3.25
662CE	24	4.0	8	3	100 ft.	80.25	45.25	3.25



Email: [sales@brgproducts.com](mailto:sales@brgproducts.com)  
Web Site: <http://www.brgproducts.com>

Copyright 2023, BRG Precision Products, All rights reserved. Printed in the USA, #62 Spec Sheet Rev.2.1, 10-30-2023



600 N River Street • Derby, Kansas 67037  
800-295-0220 • 316-788-2000  
Fax: 316-788-7080